

| Cellcore 100mm HG 50/65  |                 |            |  |
|--|-----------------|------------|--|
| Panel Depth  | Max. Clear Void | Slab Depth |  |
| 100mm  | 50mm            | 0-1940mm   |  |
| Cellcore HX S, HX B & HX Plus options are available upon request |                 |            |  |

Standard Detail

|                          |   | = aardak  |
|--------------------------|---|---|
| Products :-              | Notes :-  | = cordek  |
| Cellcore 100mm HG 50/65. | The appropriate specification of Cellcore and Heaveguard panels should be selected based upon the information provided in the relevant Cordek technical guidance. | Tel: 01403 799600   |
|                          | Cellcore panels should be installed on a smooth, flat, well compacted surface comprising of a sand / cement or concrete blinding.                                 | Email: techsupport@cordek.com                                       |
|                          | Where necessary, joints between individual Cellcore panels should be sealed using Cordek formwork tape.   | Drg. Title: Standard Slab Detail: Cellcore HG - Low Heave Potential |
|                          | <ul> <li>Care should be taken not to surcharge the Cellcore panels with either reinforcement<br/>or concrete.</li> </ul>  | Drawn: SJP  |
|                          |   | Date: June.2017 Scale: NTS Rev 002                                  |
|                          |   | Drg No.ENG/GH/CELL/100 HG 50/65/SLAB                                |